


# X1261 PROJECTOR

**DLP Technology – Value for money**

The Acer X1261 delivers, with a host of nice-to-have features for superb value. Thanks to its native XGA (1024 x 768) resolution, 2500 ANSI Lumens brightness, 3700:1 contrast ratio, a 6-segment color wheel, and Acer ColorBoost II and SmartFormat technologies, the Acer X1261 projects vivid hues and true blacks.

## Why X1261 Projector?

- Native XGA (1024 x 768)  
Maximum UXGA (1,600 x 1,200),  
1080p (1,920 x 1,080)
- Contrast Ratio 3700:1
- Brightness 2,500 ANSI Lumens  
Standard, 2,000 ANSI Lumens ECO
- Projection Distance 3.3' (1m) ~ 39.0'  
(11.9m)



SmartFormat

# Technical Specifications

<b>Model Name</b>	X1261
<b>Resolution</b>	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 (Native), 16:9
<b>Contrast Ratio</b>	3700:1
<b>Displayable Colours</b>	1.07 Billion Colors
<b>Brightness</b>	2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
<b>Projection Lens</b>	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
<b>Projection Screen Size</b>	23" (58cm) ~ 300" (762cm)
<b>Projection Distance</b>	3.3' (1.0m) ~ 39.0' (11.9m)
<b>Throw Ratio</b>	50"@2m (1.95 ~ 2.15:1)
<b>Horizontal Scan Rate</b>	30k ~ 100k Hz
<b>Vertical Scan Rate</b>	50 ~ 85 Hz
<b>Lamp Type / Life</b>	Osram 180 W user replaceable P-VIP lamp 3,000 Hours (Standard), 4,000 Hours (ECO)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical), Manual & Auto
<b>Projection Mode</b>	Front, Rear, Front-Ceiling, Rear-Ceiling
<b>Audio</b>	One Internal Speaker with 2 watts Output
<b>IR Remote Control</b>	IR remote control
<b>Digital Zoom</b>	2x
<b>Power Supply</b>	AC input 100~240V auto-switching power supply
<b>Power Consumption</b>	224 Watts (Operation), <1 Watt (Standby)
<b>Operating Temperature</b>	5°C ~ 35°C / 41°F ~ 95°F
<b>Noise Level</b>	30 dBA (Standard mode), 26 dBA (ECO mode)
<b>Input Interface</b>	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, PC Audio (Stereo mini jack) x 1
<b>Output Interface</b>	Analog RGB (D-sub) x 1
<b>Control Interface</b>	RS232 (Mini DIN) x 1
<b>Weight and Dimensions</b>	4.9 kg 268 x 192 x 80 mm (10.6" x 7.6" x 3.1")
<b>Compliance</b>	C-Tick (AS/NZS 60950)
<b>Standard Warranty</b>	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. \* Maximum hours. Actual hours depend on usage and configuration. \*\* Contact Acer for warranty details.

<sup>1</sup> Specifications vary depending on model.